

Technical Data Sheet




Product Information

Composition	Construction	Mat Size	Sq. Ft / Mat	Edge Finish	Available Thickness	Manufactured
Recycled Rubber	Mats manufactured in block form	38" x 38"	10.02	Square	22mm, 24mm, 26mm	North America
16mm Turf	Mats Laminated together	37" x 37"	9.5	Interlocking	(Both edge finishes)	
Polyurethane Binder					Custom thicknesses available	

Installation

Edge Finish	Installation Type	Layout
Square	DinoGrip adhesive	Ashlar/Brick pattern
Interlocking	Loose lay	Ashlar/Brick pattern

Product



Maintenance

Cleaner	Cleaning	Cleaning Method
DinoClean	Vacuum	Spot Clean

Sustainability

Certification Attribute	Credits
LEED Scorecard	MR2.2, MR4, MR5, EQ4.1, EQ4.3, ID1.1

Performance	Standard	Requirement	Performance vs. Requirements
TVOC Range	CDPH/EHLB v1.2-2017 (California Section 01350)	<0.5 mg/m ³	Pass
Low Emitting Adhesives	SCAQMD Rule #1168	Less than 50 g/L	Pass, 37 g/L
Recycled Content	22mm: 36% Post-Consumer Recycled Content 24mm: 41% Post-Consumer Recycled Content 26mm: 46% Post-Consumer Recycled Content		



Technical Data Sheet



Testing

Description	Test Method	Result
Tensile Strength	ASTM D2256	Material will not allow for proper tensile strength
Flammability	ASTM D2859	Pass
Fiber Thickness/Width	ASTM D3218	Thickness: 0.112 mm Width: 0.911 mm
Grab Tear Strength	ASTM D5034	Length: 375.6 lbs Width: 450.8 lbs
Melting Point	ASTM D7138	172° C melting point; indicates polypropylene
Surface Burning	ASTM E84	Flame spread: 110 Smoke Density: 950
Critical Radiant Flux	ASTM E648	0.07 W/Sq. Cm
Impact Attenuation	ASTM F1292	72° F: GMAX: 178 HIC: 995 Fall Height: 4.5'
Force Reduction	ASTM F2569	0.268
Vertical Deformation	ASTM F2569	3.1 mm

Warranty

5 - year Limited Commercial Warranty when installed in accordance with Dinoflex's Installation Guidelines.

