



TECHNICAL SPECIFICATIONS

CushionWalk[®] Paver

1. PRODUCT NAME

- Interlocking Pavers
- Non-Interlocking Pavers

2. MANUFACTURER

Dinoflex Group Limited Partnership
 P.O. Box 3309
 5590 – 46th Ave. S.E.
 Salmon Arm, B.C. Canada V1E 4S1
 Tel: 250-832-7780
 Toll Free: 877-713-1899
 Fax: 250-832-7788
 E-mail: dinoflex@dinoflex.com
www.dinoflex.com

3. PRODUCT DESCRIPTION

Composition & Materials

DINOFLEX *CushionWalk*[®] Pavers are made from a combination of 100% post-consumer recycled black SBR (styrene butadiene rubber), Pigment or EPDM (ethylene propylene diene monomer) rubber and water-based polymer binder, homogeneously mixed throughout the entire product, making the tiles superior to laminated or surface wear products.

Product Information:

| Product | Size (L x W) | Thickness | Surface Design |
|------------------------|---|--|-----------------|
| Non-Interlocking Paver | 23 ³ / ₄ " x 23 ³ / ₄ " = 3.92 ft ² 60 cm x 60 cm = 0.36 m ² | ³ / ₄ " 19 mm | Brick or Smooth |
| Interlocking Paver | 24" x 24" = 4 ft ² 61 cm x 61 cm = 0.37 m ² | ³ / ₄ " 19 mm | Brick or Smooth |

NOTE: All measurements are subject to nominal variation.

COLORS:

| | | |
|--------------|---------------------------|------------------------|
| • 100% Black | • Terra Cotta Red Pigment | • Forest Green Pigment |
| | • Stone Beige Pigment | • Teak Brown Pigment |

Note: Nominal variation in color occurs in all pigmented products. Pigmented tiles are not recommended for high traffic areas because of potential pigment loss.

| Standard Colors: | | | | |
|-------------------|-------|-------------------|----------|-------------------|
| 25% Speckled EPDM | | 50% Speckled EPDM | | 75% Speckled EPDM |
| • Green | • Red | • Beige | • Orange | • Brown |

Interlocking Pins:

#CW-TS (3/2002) 1-3 pgs © 2002 DINOFLEX Group Limited Partnership
 Revised 11/07/13
 Replaces 11/19/09

The “Interlocking” *CushionWalk*[®] Pavers are supplied with 2.5” long and 1/4” in diameter interlocking pins. These are included with every order, four per tile.

4. DESIGN & BASIC USE

DINOFLEX *CushionWalk*[®] Pavers are designed primarily for use on outdoor decks, roof top patios, walkways, cart paths, etc. Their excellent spike and slip resistant qualities contribute to the reduction of slips and falls as often seen on other types of wet surfaces.

Uses are not limited to the above.

DINOFLEX’s “Interlocking” *CushionWalk*[®] Paver provides an easy, self-aligning installation feature eliminating the requirement for adhesive.

Please contact DINOFLEX for information on custom designed logos.

5. INSTALLATION METHODS

Refer to **DINOFLEX *CushionWalk*[®] Paver Installation & Maintenance Guidelines** for information relating to sub-surfaces listed:

- 1) Concrete sub-surface
- 2) Asphalt sub-surface
- 3) Wooden sub-surface
- 4) Roofing membranes
 - a) Perimeter containment
 - b) Perimeter gluing or spot gluing
 - c) Total glue down on hard surface or filter cloth (optional)
 - d) Compacted granular base

Use adhesives recommended by DINOFLEX. Refer to **DINOFLEX *CushionWalk*[®] Paver Installation & Maintenance Guidelines** for more information.

6. INSTALLATION CONDITIONS

- a) Lay out all the tiles to be installed the next day on or near the sub-surface. Allow tiles to equalize to average ambient temperature for about 12 hours.
- b) Materials shall be protected from weather extreme temperatures, solvents, and sources of damage prior to and during installation.

7. TECHNICAL DATA

Test Standards for: American Society for Testing and Materials (ASTM)

- **ASTM C1028-89** Standard Test Method for Determining the Static Coefficient of Friction by the Horizontal Dynamometer Pull-Meter Method.
- **ASTM D395B** Standard Test Methods for Rubber Property-Compression Set.
- **ASTM D2240** Standard Test Method for Rubber Property-Durometer Hardness.
- **ASTM D412** Standard Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers-Tension.
- **CPSC FF 1-70** Surface Flammability of Carpets and Rugs.

Physical / Chemical Properties

| TEST PROCEDURE | DESCRIPTION | ACHIEVED VALUES (Subject to nominal variation) |
|-----------------------|--------------------------------|--|
| ASTM C1028-89 | Static Coefficient of Friction | Dry .62 |
| ASTM D395B | Compression Set Under Force | 91% recovered |
| ASTM D2240 | Hardness Shore A Durometer | 61 Indentation hardness |
| ASTM D412 | Tensile Strength | 299 lbs/sq. in. |
| CPSC FF 1-70 | Surface Flammability | 3.6 in. uncharred area |

Copies of test reports and additional product information are available upon request.

8. INSTALLATION & MAINTENANCE PROCEDURES

Use a qualified or certified installer with experience installing similar recycled rubber paver products. Refer to Dinoflex “*CushionWalk*® Paver Installation & Maintenance Guidelines”.

- Toll Free Tel: 877-713-1899
- Direct Line: 250-832-7780
- Fax: 250-832-7788
- www.dinoflex.com

9. AVAILABILITY & COST

Availability

Please, contact the dealer, distributor, or Dinoflex for information on availability.

Cost

Pricing information may be obtained from dealer, distributor, or Dinoflex.

10. WARRANTY

The standard warranty period is 5 years from date of shipment. Please, see DINO FLEX’s limited warranty for particulars of coverage.

11. TECHNICAL SERVICES

Contact Dinoflex for more information, where a staff of trained customer service personnel offers design assistance and technical support.

12. FILING SYSTEMS

- Architectural Product Information Binder
- www.dinoflex.com