



**GENERAL CLEANING & MAINTENANCE EXTERIOR PRODUCTS  
ROUTINE MAINTENANCE EXTENDS LIFE AND ENHANCES APPEARANCE.**

**A) Initial Cleaning:**

The tiles are coated with water-based mold release residue, a natural result of the manufacturing process. This will initially cause slight discoloration and slipperiness. For fast removal, apply a solution of neutral cleaner (e.g. DinoClean) and agitate with brush or mop, then rinse with water. Otherwise, let mold release wear off with time, which could take up to four weeks.

**KEEP MOVEABLE FURNISHINGS, PLANTERS, ETC OFF NEWLY INSTALLED SURFACE FOR A MINIMUM OF 48 HOURS. THIS WILL ALLOW ALL PAVERS/TILES TO BE EXPOSED TO UV LIGHT AND ENSURE EVEN INITIAL COLOR ADJUSTMENT.**

**B) Ongoing Maintenance:**

Sweeping and hosing off the surface are the most common methods of keeping the pavers/tiles clean. If surface is excessively dirty, apply a solution of neutral cleaner and water and agitate with a brush. Then rinse with garden hose. **Do not use a pressure washer to clean pavers/tiles. Do not use solvents of any kind.**

**DINOFLEX DOES NOT ASSUME ANY RESPONSIBILITY FOR DAMAGES CAUSED BY CHEMICAL ADDITIVES.**

**Thank you for choosing Dinoflex exterior tile products. If you have any questions, please contact us at our factory at 1-877-713-1899.**

**DINOFLEX Group Limited Partnership  
P.O. Box 3309  
5590 – 46<sup>th</sup> Ave SE  
Salmon Arm, B.C. V1E 4S1 Canada**

**Tel: (250) 832-7780  
Fax: (250) 832-7788  
Toll Free Tel: 1-877-713-1899  
E-mail: [sales@dinoflex.com](mailto:sales@dinoflex.com)**

**[www.dinoflex.com](http://www.dinoflex.com)**