



Evolution **COMMERCIAL** by dinoflex

The Next Generation In Design

OFFICES ■ EDUCATION ■ MUSEUMS ■ RETAIL ■ LIBRARIES



RECYCLED
RUBBER
FLOORING

Commercial flooring has evolved from traditional carpet and hard surfaces to our luxurious Evolution recycled rubber flooring. Designers can bring their visions to life with brilliant colors creating a space that is cohesive and functional while standing the test of time. When you combine these striking color blends with high traction, underfoot comfort and superior sound reducing properties, this hardwearing, sustainable rubber flooring is perfect for a wide range of commercial applications. Experience the next generation in design.



Design and
Durability
Converge.

Evolution Commercial Flooring is durable and attractive, and made with the best quality EPDM to ensure low odor and maximum color vibrancy. With over 70 colors to choose from, we have a unique solution to suit any design.

Features

- FloorScore® certified for indoor air quality
- High traction even when wet
- Made from recycled commercial grade truck tires
- Block manufacturing creates a higher density product
- Sound reducing properties
- Offers enhanced under foot comfort
- Stain-resistant
- 70+ standard designer colors to choose from with no minimums

Benefits

- Ensures a healthy breathing environment
- Reduces risk of slip and falls
- Environmentally friendly and helps to contribute to the Green Credit program
- A durable product that won't show wear patterns and is guaranteed never to curl
- Makes for a quieter space
- Reduces the effect of stress on knees, hips, back and feet caused by prolonged standing
- Looks newer longer
- No MOQ allows designers to utilize multiple colors to create a customized installation pattern

Best For

Commercial Retail
Community Centers
Education

Fitness Centers
Health Care
Hospitality

Libraries
Museums
Offices



Color: Arctic Night

Tolerance of +/- 0.5mm

Square Edge Glue Down

38" x 38" = 10.0ft²
(96.5cm x 96.5cm = 0.93m²)

STANDARD THICKNESS


4mm (5/32")	7 mm (9/32")
5mm (3/16")	8mm (5/16")
6mm (1/4")	9mm (11/32")

Interlocking Loose Lay

37" x 37" = 9.5ft²
(94cm x 94cm = 0.88m²)


STANDARD THICKNESS

7 mm (9/32")
8mm (5/16")
9mm (11/32")




Color Swatches


evo50




CASINO ROYALE




DREAM CATCHER




FIRE FLY



MOON BEAM



NEBULUS



PURPLE RAIN




RAIN FOREST



SAPPHIRE HAZE



SMOKY AZURE




SPANISH MOSS




STONE GROUND

evo60




AUTUMN
WHISPER




BLACK ICE



BRUSH FIRE




BURNING
EMBERS



CRACKED PEPPER



DOGWOOD



DRAGONFLY




DRIFTWOOD




FLAMENCO



IRISH MOSS



MARDI GRAS



MESQUITE




MOLTEN LAVA




MUSKWOOD



PIXIE MOSS



RIO GRANDE



RIP TIDE




ROSEWOOD



SAGE

evo70



ADOBE



ARCTIC NIGHT




BAKED CLAY




CORKWOOD



COTTON CANDY




FIRESTORM




IMPERIAL



MUDDY WATER




NORDIC FOG



SPUN SILVER



TWILIGHT MIST




WIND CHILL


evo80




BELL PEPPER




BLUEBERRY TWIST



CALYPSO BLUE



CALYPSO GREEN




CALYPSO RED




CLEAR WATERS




GLACIER ICE



GRAPE TWIST



GREEN PEPPER




ICEBERG



ICICLES




JALAPENO
PEPPER




LEMON PEPPER



NIAGRA MIST



NORTHERN
LIGHTS



PLUM TWIST



SANDALWOOD



SNOW DRIFT




UNIVERSE


evo90



BANANA SPLIT



FIREWEED




FIREWORKS




HOT SALSA



RED PEPPER




SUNFLOWER



SWEET PEPPER



TIDAL POOL



WILD FLOWERS



YELLOW PEPPER

Contact your Sales Representative for more information.

Colors shown are reproduced as closely as possible to actual product. Contact Dinoflex for product sample.



Click here to design your own
Recycled Rubber Tile.



Testing Results

DESCRIPTION	TEST METHOD	OVER 50% COLOR
Electrostatic Propensity	AATCC	Maximum Average Voltage = Negative 2.1 KV
Accelerated Floor Trafficking		None
Sound Absorption / Noise Reduction Coefficient	ASTM C423	SAA - 0.06 NRC - 0.05
Taber Abrasion	ASTM C501	Weight Loss 1.05 grams
Compression Set Under Force	ASTM D395B	94.7% Recovered; 5.3% Unrecovered
Breaking Load / Elongation / Tenacity	ASTM D412	Breaking Load: 73.7lbs - 119.5lbs
		Elongation: 69.9% - 117.6%
		Tenacity: 186.1lbs/square inch - 292.2lbs/square inch
Static Coefficient of Friction	ASTM D2047	Dry 0.85; Wet 1.01
Hardness Shore A Durometer	ASTM D2240	59 - 62
Surface Flammability	ASTM D2859	PASSES
Density Foam Test	ASTM D3676	78.3 lbs/cu. ft.
Impact Sound Transmission (with Plenum)	ASTM E492	4mm IIC 56; 8mm 4IIC 59
Critical Radiant Flux	ASTM E648	CRF 0.23 watts/square cm (4mm 80% EPDM)
		CRF 0.22 watts/square cm (6mm 75% EPDM)
		CRF 0.37 watts/square cm (6mm High Color)
Critical Radiant Flux (15 min burn)	ASTM E648 (NY)	CRF 0.59 watts/square cm (4mm 70% EPDM)
		CRF 0.58 watts/square cm (4mm 80% EPDM)
Smoke Density	ASTM E662	Flaming 287; Non-Flaming 339
Flexibility	ASTM F137	6mm Mandrel PASS
Electrical Resistance - Surface to Ground	ASTM F150	1.9 x 10 ¹¹ Ohms (average)
Electrical Resistance - Surface to Surface	ASTM F150	3.9 x 10 ¹¹ Ohms (average)
Chemical Resistance	ASTM F925	No Change
Chemical Resistance - Liquid Nitrogen (5 min & 24 hr)	ASTM F925	No Change
Static Load (1000 lbs)	ASTM F970	0.042 inch (10.6%) residual compression
Short Term and Residual Indentation (@ 140 lbs)	ASTM F1914	-0.030 Inch (9.0%) Residual Indentation
Mildew Resistance	ASTM G21	No Mildew After 28 Days
Hot Metal Nut Test Fully Adhered	BS 4790	Fully Adhered & Loose Laid - PASS

Please Note: All measurements are subject to nominal variation.

Dinoflex
P.O. Box 3309
5590 46 Ave SE
Salmon Arm, BC, Canada
V1E 4S1

Toll Free: 1-877-713-1899
Direct: 250-832-7780
sales@dinoflex.com
dinoflex.com



10-year limited warranty
when installed in accordance with
Dinoflex's Installation Guidelines.

Date Issued: April 2025