

A person is shown from the waist down, wearing a green and white striped sweater and dark pants. They are sitting on a dark, textured floor and are in the process of tying a white roller skate. The skate has a white sole and a black upper. The person's hands are visible, and the laces are being pulled through the eyelets.

Vulca-NO! SKATE

by dinoflex

INDOOR ARENA ■ OUTDOOR ARENA



RECYCLED
RUBBER
FLOORING

A low-angle, dramatic shot of ice hockey players in a tunnel, looking towards a bright light at the end. The players are wearing full gear, including helmets and skates. The tunnel walls are metallic and show signs of wear. A large, dark, circular inset in the lower-left corner shows a close-up of the dark, textured surface of the Vulca-NO! Skate flooring.

The ultimate solution for skate-resistant flooring. Vulca-NO! Skate is specifically designed for arena applications, combining unmatched durability with superior safety. Its non-vulcanized composition ensures a low-VOC, chemical-free surface while offering exceptional impact absorption.

Good for athletes.
Great for floors.

Built to endure heavy foot traffic and frequent skate use, Vulca-NO! Skate provides a reliable, long-lasting flooring solution that keeps your facility both protected and environmentally conscious.

Features

- Great traction - wet or dry
- Heavy duty dense material
- Impact absorbing
- Sound reducing
- Non-vulcanized
- Easy to clean

Benefits

- Reduces risk of injuries from slips & falls
- Eliminates the need to replace frequently
- Reduces soreness, fatigue in muscles & joints
- Decreases vibration & noise
- Certified for indoor air quality with no odor
- Low maintenance costs

Best For

Arena Corridors
Locker Room

Penalty Box
Player Box

Wet Locker Room Area




Tolerance of +/- 0.5mm

***Available only in black**

Square Edge

48" x 72" = 24ft²
(121.92cm x 182.88cm)



STANDARD THICKNESS

7mm (9/32"), 12mm (1/2"), 15mm (19/32"),
19mm (25/32")



Testing Results

DESCRIPTION	TEST METHOD	RESULT
Breaking Load & Elongation - 12mm	ASTM D412	Breaking load: 115.89 Lbs. Elongation: 137.02% Tensile: 479.9 lbs/sq. inch
Coefficient of Friction: James Machine	ASTM D2047	Dry = 1.12, Wet = 1.05
Taber Abrasion	ASTM D4060	0.20 Grams (0.19%) loss
Flexibility	ASTM F137	Passes - 6mm Mandrel
Static Load Limit	ASTM F970	0.005 Inch @ 250 psi
Dimensional Stability/Curling Properties	ASTM F2199	Length: -0.010" per 12 inches Width: -0.019" per 12 inches
Force Reduction	ASTM F2569	11.3%, Class 1
Force Reduction Ball Rebound Surface Finish Effect Vertical Deflection / Deformation	ASTM F2772	Force Reduction: 11.3% Class 1 Ball Rebound: 98.5% Passes Surface Finish Effect: 104 BPV Passes Vertical Deflection/Deformation: 0.6 mm Class B
Slip Resistance	BM-III British Pendulum Skid Friction Coefficient Tester	Average COF: Dry = 0.83, Wet = 0.38

Please Note: All measurements are subject to nominal variation.

Dinoflex
P.O. Box 3309
5590 46 Ave SE
Salmon Arm, BC, Canada
V1E 4S1

Toll Free: 1-877-713-1899
Direct: 250-832-7780
sales@dinoflex.com
dinoflex.com

5-year limited warranty
when installed in accordance with
Dinoflex's Installation Guidelines.

Date Issued: September 2025

